Ceiling LED pendants.

CH3128 INSTALLATION SHEET

Please Note:

- All Kuzco LED fixtures come with pre-wired LED module(s).
- Unless instructed to do so, please do not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage.
- For dimming, an ELV (Electronic Low Voltage) dimmer is required.
- Remove the fixture from its original packaging. Remove the canopy mounting bar from within the canopy by removing the decorative nuts. Secure the mount plate (with canopy screws facing downward) to the reinforced junction box.
- Before you mount the canopy to the mounting plate please select the desired lengths you wish the pendants to hang. To shorten the cable just pull the cables up into the canopy (2a). Once you have adjusted the wires to the desired lengths, move all the wire grips down each wire from inside the canopy to where the wire passes through the canopy, now secure.
- You are now ready to mount the canopy to the mounting plate first connect all wires correctly L live wire (white to white) N neutral wire (black to black) and G ground (green to green) with provided marrets from the hardware package 3a). Align the threaded scews hanging downward from the mounting plate to the holes inside the canopy. Push the canopy up towards the ceiling so the two scews point through the hole in the canopy. You can then screw on the decorative nut (3b) onto the threaded bar pointing through the canopy to securely install the canopy to the mounting plate.
- LED Engines are built in. Push the glass (4a) up to the LED engines (4b) and thread turning clockwise.
- You have now completed the installation of your fixture, enjoy.

START FROM HERE

- Make sure power is completely off at the fuse box.
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in clear area.
- Wear gloves at all times during this installation.
- Read instructions carefully before you start assembly.
- Keep this instruction sheet for future reference.

Technical Support: 1-855-855-8926

