Ceiling LED Chandelier



START FROM HERE

- Make sure POWER is COMPLETELY OFF at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all times during this installation
- · Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

Technical Support: 1-855-855-8926

Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- Use ELV (Electronic Low Voltage) or TRIAC type of dimmer for dimming application
- 120V input

- **1.** Remove fixture from its original package.
- **2.** Separate mounting plate (1c) from canopy (2a) by removing canopy screws with allan key (2f).
- **3.** Attach mounting plate **(1c)** to electrical junction box **(1a)** using screws provided **(1e)** in hardware package.
- **4.** Secure mounting plate (1c) to mounting surface with anchors (1f) and screws (1g)
- Make sure Aircraft Cable (2e) is securely attached between canopy (2a) and mounting plate (1c). Determine hanging height of fixture by securing rods (2d) to canopy (2a) and fixture body (3b) after feeding fixture wires (LED+ and LED-) through rods.
- **6.** Make proper electrical connections between LED and DC driver, LED- Negative (black), LED+ Positive (White) using quick connector provided (2g) (See Illustation 1 and refer to diagram on driver)
- **1.** Make proper electrical connections (Black to Hot "L", White to Neutral "N", Green to ground with orange wire nuts **(1b)** provided in hardware package
- **8.** Secure canopy (2a) to mounting plate (1c) with canopy screws (2f) using allan key
- **9.** Align, insert mounting hardware on back of shade (3a) onto fixture mounting plate (3c), rotate clockwise slightly to secure shade



